Data scraping, ingestation, and modeling: bringing cars.com into the intro stats class

Nicholas J. Horton

Department of Mathematics and Statistics Amherst College, Amherst, MA, USA

CAUSE webinar, November 21, 2017

nhorton@amherst.edu http://nhorton.people.amherst.edu https://github.com/Amherst-Statistics/Cars-Scraping-Webinar

- Danny Kaplan (for the original idea)
- Project MOSAIC: Danny Kaplan (Macalester College), Randy Pruim (Calvin College), Ben Baumer (Smith College), and Johanna Hardin (Pomona College)
- NSF # 0920350

Goal

- I will describe a classroom activity where pairs of students hand scrape data from cars.com, ingest these data into R, then carry out analyses of the relationships between price, mileage, and model year for a selected type of car.
- This early in the semester activity can help illustrate the statistical problem solving process.
- The "Less Volume, More Creativity" approach utilized by the mosaic package facilitates the analysis with a minimal amount of syntax.
- Key concepts that are introduced and reinforced including data ingestion, multivariate thinking through graphical visualizations, and regression modeling.
- Extensions and additional use of the dataset will be discussed along with potential pitfalls.

Cars, cars, and more cars



24 Photos/Video

2012 MINI Cooper Base

Highclass Gray Metallic, 2 door, FWD, Convertible, 6-Speed Manual, 1.6L I4 16V MPFI DOHC, Stock# MI265375.

Autobahn USA ~ 47 mi. away 888-233-5057 Email Dealer

Save/Compare

Free CARFAX Report



15 Photos/Video

2011 MINI Cooper Base

Midnight Black Metallic, 2 door, FWD, Hatchback, Automatic, 1.6L I4 16V MPFI DOHC, Stock# 093365.

Cohasset Imports ~ 87 mi. away 888-586-6530 Email Dealer

Save/Compare

Free CARFAX Report

2012 MINI Cooper Base

\$22,165

Nicholas J. Horton cars.com and intro stats

\$22,500

\$22,500 9.844 mi.

13,370 mi.

- How much do cars cost?
- How much do car prices vary?
- How are car prices associated with mileage?
- How are car prices associated with age?
- How quickly do new cars depreciate?
- How much does it cost for a car to drive a mile?

Guidelines for Assessment and Instruction in Statistics Education (GAISE) College Report 2016

• Teach statistical thinking.

- Teach statistics as an investigative process of problem-solving and decision-making.
- Give students experience with *multivariable thinking*.
- Pocus on conceptual understanding.
- Integrate real data with a context and purpose.
- Isster active learning.
- **I** Use technology to explore concepts and analyze data.
- **O** Use assessments to improve and evaluate student learning.

- We live in a multivariate world
- If intro stats only addresses bivariate questions (e.g., two-sample t-test) we risk becoming irrelevant
- Straightforward to consider multivariate visualizations and fit multiple regression models (Project MOSAIC "Less Volume, More Creativity")
- *R Journal*: https: //journal.r-project.org/archive/2017/RJ-2017-024

Groups of size two Duration one or two 50-minute class periods Requirements one computer per student Software R/RStudio and Excel or Open Office Motivation Why might we care about car prices?

Cars.com Activity

Group is given a major city in the US (e.g., Atlanta or Los Angeles)

- Person 1 searches cars.com for used Toyota Prius cars on offer within 50 miles of that city
- Person 2 downloads the template cars.csv spreadsheet and open it up on their computer
- Person 1 reads out car models, year, mileage, and price
- Person 2 enters the values into the spreadsheet and reads them out for Person 1 to check
- Continue until 40 cars have been entered (note that some groups will be really slow, so may only yield 20-25 cars)
- Person 2 emails Person 1 the cars.csv spreadsheet then both members upload this into RStudio

- The file student.Rmd reads cars.csv
- Generates descriptive statistics (for data quality assessment, e.g., using \$ in price)
- Create visual multivariate displays (e.g., mileage by year)
- Fit regression model and display coefficients

Cars.com analysis (part 2)

- Once student.Rmd runs without error, the creative step begins
- Students need to find an interesting display and fit a multiple regression model
- Goal is to make an insight
- Publish this on rpubs.com using a class-wide login provided by the instructor
- Quickly review several of these to see insights
- Deliverable: full credit for email to instructor (cc-ed to group partner) of modified student.Rmd and cars.csv files

glimpse(ds)

- ## Observations: 40
- ## Variables: 6
- ## \$ car <fctr> Toyota Prius, Toyota
- ## \$ model <fctr> Two, Two, Four, Four,
- ## \$ price <dbl> 21950, 20887, 19998, 1
- ## \$ year <int> 2016, 2016, 2013, 2014
- ## \$ mileage <int> 6255, 9997, 30322, 462
- ## \$ location <fctr> Atlanta, Atlanta, Atl

favstats(~ price, data=ds)

min Q1 median Q3 max mean sd n mis: ## 13999 14596 14981 15999 21950 15743.92 1965.711 40

favstats(~ mileage, data=ds)

min Q1 median Q3 max mean sd n mi ## 6255 32688.25 40002 49950 63546 40057.38 14701.67 40

Examples

gf_boxplot(price ~ as.factor(year), data=ds)



æ

- ● ● ●

Examples



- Collate individual group data into carscollated2017.csv
- Perform data cleaning (e.g., numeric zip code rather than city)
- Add location to the multiple regression model
- Practice interpreting regression models with categorical predictors
- Practice interpreting regression models with interactions between mileage and year
- Seek insights: depreciation dramatic for new cars

A used car is best bet

By Tom and Ray Magliozzi Published: Oct. 26, 2001 12:00 a.m. Updated: Oct. 26, 2001 10:42 a.m.



・ロト ・日下・ ・日下・

Leave a comme

2

Question: My beautiful, normally intelligent wife of 24 years and I disagree mightily about the best timing to buy and sell a vehicle. We're absolutely positive we're each right, and we're absolutely positive the other is wrong. The argument involves economics — how to spend the least amount of money. I say you should buy a car with about 60,000-80,000 miles on it and drive it into the ground. She thinks it's better to buy a 1- or 2-year-old car and keep it only for two or three years. It's time to replace my "driven into the ground" '87 Nissan pickup, and we need your advice. — Kurt Tom: It's great to get letters from lovebirds like you two, Kurt. If this is all you've got to argue about, things must be pretty good.

Ray: Here's the story. Speaking from a purely economic point of view — how you spend the least amount of money on cars — you're more correct than she is. If you buy an old car, which has already taken the bulk of its depreciation hit, and then drive it into the ground, you will spend the least.

Tom: We actually wrote a pamphlet about this very subject, called "How to Buy a Great Used Car: What Detroit and Tokyo Don't Want You to Know." In it, we lay out several money-saving used-car strategies, and we prove mathematically that the "heap strategy" is the cheapest. If tally(~ year, margins=TRUE, data=ds)

##	year									
##	2007	2010	2011	2012	2013	2014	2015	2016	2017	Total
##	2	5	37	45	176	237	201	126	2	831

tally(~ location, margins=TRUE, data=ds)

##	location			
##	40202	Atlanta	Bangor, ME	Baton Rouge
##	40	40	40	40
##	Buffalo	Chicago	Cleveland	Dallas
##	40	41	26	41

/⊒ > < ∃ >

э

Cars.com followup

##	locationSeattle	2136.54194	463.06079
##	locationTampa	-2152.29736	462.16712
##	mileage	-0.06065	0.00950
##	as.factor(year)2012	-251.31079	1135.10846
##	as.factor(year)2013	3237.23166	894.68539
##	as.factor(year)2014	3140.19070	888.34344
##	as.factor(year)2015	3252.51391	885.30630
##	as.factor(year)2016	8208.61054	874.47684
##	<pre>mileage:as.factor(year)2012</pre>	0.01709	0.01436
##	mileage:as.factor(year)2013	-0.01797	0.01215
##	mileage:as.factor(year)2014	-0.00343	0.01396
##	<pre>mileage:as.factor(year)2015</pre>	-0.00989	0.01393
##	mileage:as.factor(year)2016	-0.18186	0.02754
##			
##	Residual standard error: 204	40 on 790 de	grees of fre
##	Multiple R-squared: 0.736,	Adjusted R	-squared: 0

F-statistic: 71.2 on 31 and 790 DF, p-value: <2e-1

Cars.com followup

```
carfun <- makeFun(mod)
carfun(year=2016, mileage=1000, location='Tampa')</pre>
```

1 ## 22875

carfun(year=2016, mileage=1000, location='Tampa') carfun(year=2016, mileage=1001, location='Tampa')

1 ## 0.2425

carfun(year=2012, mileage=1000, location='Tampa') carfun(year=2012, mileage=1001, location='Tampa')

1 ## 0.04355

Cars.com followup



- Interpreting model is a great exam question
- Residual diagnostics
- Outlier detection
- Account for different car models (sparsity and inconsistent coding)
- Automate data scraping

- Ensure that students see multivariate examples early and often
- Ensure that students use real tools
- Once they have some experience with "tame data", have them ingest their own
- Motivate automated data scraping procedures
- Practice composing and answering questions with data

Data scraping, ingestation, and modeling: bringing cars.com into the intro stats class

Nicholas J. Horton

Department of Mathematics and Statistics Amherst College, Amherst, MA, USA

CAUSE webinar, November 21, 2017

nhorton@amherst.edu http://nhorton.people.amherst.edu https://github.com/Amherst-Statistics/Cars-Scraping-Webinar